

1 TITLE OF THE INVENTION

2 **Multi-Network Communications System**

3 BACKGROUND OF THE INVENTION

4 Field of the Invention

5 The present invention relates generally to communications networks
6 and more specifically to a multi-network communication system in which the
7 user can select one of a plurality of communications networks owned and
8 operated by different service providers.

9 Description of the Related Art

10 There are a number of communications networks owned and operated
11 by different service providers. Users compare the service features of the
12 networks to select one that meets their desired feature and purchase a mobile
13 terminal of the selected network. In a service area where networks of
14 different service providers co-exist, one network may be carrying heavy
15 traffic while another is carrying light traffic with a sufficient remaining
16 capacity to handle new calls. In such instances, it is desirable for users to
17 access the light-traffic network. To meet this objective, a multi-network user
18 terminal has been developed to allow the user to use a desired one of the
19 networks the terminal can access. However, none of these networks sends
20 back a response signal that indicates the current level of network traffic.
21 Therefore, the user has to arbitrarily choose one network and makes a call
22 attempt. If congestion is encountered, the user abandons the call and
23 switches over to another network and repeats the same process. The process
24 may be repeated until the user encounters a network that can complete the
25 call.

1 Therefore, a need does exist to provide a multi-network environment
2 that allows users to receive services from a number of communications
3 networks without the need for making a manual switchover from one
4 network to another.

5 SUMMARY OF THE INVENTION

6 It is therefore an object of the present invention to provide a multi-
7 network communications system in which the user can access a desired
8 network.

9 According to a first aspect, the present invention provides a method of
10 establishing a connection to a desired communications network, comprising
11 the steps of sending a request signal to each of a plurality of communications
12 networks, receiving response signals from the networks, indicating the
13 received response signals, allowing a user to select one of the networks based
14 on the indicated response signals, and establishing a connection to the
15 selected communications network.

16 According to a second aspect, the present invention provides a
17 communication terminal comprising a network interface for sending a
18 request signal to each of a plurality of communications networks and for
19 receiving response signals from the networks, and a user interface for
20 indicating the received response signals to allow a user to enter a command
21 signal based on the indicated response signals and selecting one of the
22 networks according to the entered command signal. The network interface
23 establishes a connection to one of the networks which is selected by the user
24 interface.

25 According to a third aspect, the present invention provides a
26 communication system comprising a plurality of wireless networks and a

1 user communication terminal. Each of the wireless networks produces a
2 response signal upon receipt of a request signal. The user communication
3 terminal comprises a wireless interface for sending request signals to the
4 wireless networks and for receiving response signals from the networks. A
5 user interface indicates the received response signals to allow the user to
6 enter a command signal and selects one of the wireless networks according to
7 the entered command signal. The wireless interface establishes a connection
8 to one of the communications networks which is selected by the user
9 interface.

10 According to a fourth aspect, the present invention provides a method
11 of performing a handover operation, comprising the steps of sending a
12 handover request signal to each of a plurality of wireless networks, receiving
13 response signals from the wireless networks, the response signals indicating
14 respective traffic congestion levels of the wireless networks, selecting one of
15 the wireless networks based on the response signals received from the
16 networks, and establishing a connection to the selected wireless network.

17 According to a fifth aspect, the present invention provides a mobile
18 terminal comprising a wireless interface for sending a handover request
19 signal to each of a plurality of wireless networks and receiving response
20 signals from the wireless networks, the response signals indicating respective
21 traffic congestion levels of the networks, and control circuitry for selecting
22 one of the wireless networks based on the received response signals. The
23 wireless interface establishes a connection to the wireless network selected by
24 the control circuitry.

25 According to a sixth aspect, the present invention provides a
26 communication system comprising a plurality of wireless networks, each of

1 said networks producing a response signal upon receipt of a handover
2 request signal which indicates traffic congestion level of the network, and a
3 wireless terminal. The wireless terminal comprises a wireless interface for
4 sending the handover request signal to the wireless networks and receiving
5 the response signals from the wireless networks. Control circuitry selects one
6 of the wireless networks based on the received response signals. The wireless
7 interface establishes a connection to one of the wireless networks which is
8 selected by the control circuitry.

9 According to a seventh aspect, the present invention provides a
10 method of establishing a connection to a selected network. The method
11 comprises the steps of receiving, at a first communications network, a
12 connection request from a user terminal, sending a request signal from the
13 first communications network to a traffic management center if the
14 connection request encounters a traffic congestion, sending a rerouting
15 message from the center to the user terminal via the first communications
16 network for identifying a second communications network whose congestion
17 level is lower than a predefined threshold level to thereby allow a user to
18 send a connection request to the second communications network.

19 According to an eighth aspect, the present invention provides a
20 communication system including a traffic management center, and a plurality
21 of communications networks. A first one of the communications networks
22 receives a connection request from a user terminal and sends a request signal
23 to the traffic management center when a traffic congestion is encountered in
24 the first communications network. The traffic management center responds
25 to the request signal by sending a message to the requesting network
26 identifying a second one of the networks whose congestion level is lower

1 than a predetermined threshold level. The message sent from the center is
2 retransmitted to the user terminal to allow the user to switch to the second
3 communications network.

4 BRIEF DESCRIPTION OF THE DRAWINGS

5 The present invention will be described in detail further with reference
6 to the following drawings, in which:

7 Fig. 1 is a block diagram of a multi-network communication system
8 according to the present invention;

9 Fig. 2 is a flowchart of the operation of a user terminal according to a
10 first embodiment of the present invention;

11 Fig. 3 is a flowchart of the operation of a communications network
12 according to the first embodiment of this invention;

13 Fig. 4 is a flowchart of the operation of a user terminal according to a
14 second embodiment of the present invention;

15 Fig. 5 is a flowchart of the operation of a wireless network according to
16 the second embodiment of this invention;

17 Fig. 6 is a block diagram of a second embodiment of the multi-network
18 communication system of the present invention;

19 Fig. 7 is a flowchart of the operation of a communication network
20 according to the second embodiment of the present invention; and

21 Fig. 8 is a flowchart of the operation of a traffic management center
22 according to the second embodiment.

23 DETAILED DESCRIPTION

24 In Fig. 1, there is shown a user terminal 10 which can selectively access
25 to a plurality of wireless communication networks 11, 12 and 13, which are

1 respectively owned and operated by different service providers. User
2 terminal 10 is either a mobile terminal of cellular phone network or a fixed
3 terminal of a wireless network connected by a fixed wireless access (FWA)
4 system, for example.

5 As will be described, the user at the terminal 10 selects a desired
6 network according to response signals received from the wireless networks
7 11, 12 and 13. For this purpose, the user terminal 10 is essentially comprised
8 of a wireless interface 21, a controller 22 and a user interface 23. Controller 22
9 directs the wireless interface 21 to send a request signal to and receive a
10 response signal from each wireless network. User interface 23 includes a
11 display and an annunciator for indicating the received response signal to
12 permit the user to select a desired network and enter a command signal.
13 Controller 22 directs the wireless interface 21 to establish a connection to the
14 network which is selected by the user interface 23.

15 Each of the wireless networks is essentially comprised of a wireless
16 interface 31, a controller 32, a memory or database 33 and a traffic monitor 34.
17 Database 33 stores network service information such as tariff of the network.
18 Traffic monitor 34 constantly monitors the network for detecting the traffic
19 congestion level of the network. In response to a request signal from the user
20 terminal 10, the controller 32 of an accessed wireless network reads tariff data
21 from the database 33 and formulates a response signal with the tariff data
22 and the congestion level detected by the traffic monitor 34 and transmits the
23 response signal to the requesting user terminal 10.

24 These wireless networks have different tariffs and traffic handling
25 capacities. For example, the wireless network 11 has lowest phone rate and

1 lowest traffic handling capacity (i.e., highest congestion level), the wireless
2 network 12 has medium phone rate and medium traffic handling capacity
3 (i.e., medium congestion level), and the wireless network 13 has highest
4 phone rate and highest traffic handling capacity (i.e., lowest congestion level).

5 According to a flowchart shown in Fig. 2, the operation of the
6 controller 22 proceeds by initially setting a network identifying variable "i" to
7 1 at step 101. Controller 22 selects a network (i) at step 102 and sends a
8 request signal to the selected network for requesting it to send a phone rate
9 schedule of the network and the current traffic level (step 103).

10 In Fig. 3, the network identified by the variable "i" responds to the
11 request signal (step 201) and reads the tariff data from the database 33 and
12 causes the traffic monitor 34 to detect the current traffic level of the network
13 (step 202) and formulates and sends a response signal to the requesting user
14 to communicate the tariff and congestion data.

15 In Fig. 2, the user terminal receives the response signal at step 104.
16 The response signal is converted by the controller 22 into a vocal
17 announcement which is supplied to an annunciator or converted to textual
18 data which is supplied to display unit (step 105). If all networks are not
19 tested (step 106), the variable "i" is incremented by one at step 107. Steps 102
20 to 105 are repeated on the next wireless network until requested information
21 are obtained from all networks.

22 If all networks have been tested, flow proceeds from step 106 to step
23 108 to prompt the user to enter a command signal for selecting one of the
24 communications networks. When a select command is entered from the user
25 interface 23 at step 109, the controller 22 directs the wireless interface 21 to

1 establish a connection to the selected network (step 110).

2 The present invention can be advantageously used to perform a
3 handover when communication signals transmitted from the user terminal 10
4 fall below a critical level during a call.

5 Fig. 4 is a flowchart of the operation of the user terminal 10 when the
6 communicating wireless network is performing a handover. When the
7 mobile terminal detects that a handover operation is in progress (step 301), a
8 variable "j" is incremented by 1 at step 302. Variable "j" identifies a wireless
9 network other than the network with which the mobile terminal is currently
10 in communication. Mobile terminal 10 selects a base station of the wireless
11 network (j) at step 303 and sends a handover request signal to the selected
12 network (step 304).

13 In Fig. 5, the network identified by the variable "j" responds to the
14 handover request signal (step 401) and detects the current traffic level of the
15 network with its traffic monitor (step 402) and sends a response signal to the
16 requesting user to inform the detected congestion level (step 403).

17 In Fig. 4, the requesting user terminal receives the congestion level
18 indicating signal from the selected network (step 305). Steps 303 to 305 are
19 repeated on surrounding base stations of other wireless networks by
20 incrementing the variable "j" by one at step 307 until all surrounding base
21 stations have been tested (step 306).

22 At step 308, the user terminal selects one of the wireless networks
23 whose congestion level is of the lowest value and establishes a handover
24 connection to the base station of the selected wireless network (step 309).

25 The present invention can also be implemented in a different

configuration as shown in Fig. 6 in which a user terminal 20 can operate in multiple modes. In a mobile mode, the user terminal is served by a wireless network 21 and in a fixed mode it is served by an optical network 22 or a metallic wireline (copper or coaxial) network 23. User terminal 20 is essentially comprised of a wireless interface 41, an optical line interface 42 and a wireline interface 43 for establishing a connection to the wireless network 21, the optical network 22 and the wireline network 23, respectively. A controller 44 is provided between the interfaces 41, 42, 43 and a user interface 45.

A traffic management center 50 is provided, which includes a user-information database 52, a routing database 53 and a controller 51 connected to both databases. Networks 21, 22 and 23 are also connected to the controller 51. The information stored in the database 52 identifies networks to which registered users are accessible. Routing database 53 maintains cost data indicating the cost of a call routed through each of the networks 21, 22, 23 to a particular destination. Controller 51 monitors networks 21, 22 and 23 to detect their congestion levels. If a request signal is received from a user terminal via one of the networks, the controller 51 reads the information of the requesting user from the database 52 and determines whether the user is accessible to other networks. If this is the case, the controller 51 returns a response signal to the user terminal to indicate another network as an alternate route if the congestion level of the current network exceeds some threshold level.

In operation, the user initially selects one of the communications networks 21, 22 and 23. If the selected network is the wireless network 21,

1 the user establishes a wireless link via wireless interface 41 to a base station
2 by manipulating the operating keys of the user terminal. If the initially
3 selected network is one of networks 22 and 23, the user attaches the user
4 terminal 20 to the line terminal of the selected network through the
5 corresponding line interface 42 or 43 and establishes a connection to the
6 selected network. Such line terminals may be provided in a public telephone
7 booth or an office environment in which users can access a number of
8 different networks via a private branch exchange.

9 The operation of each of the networks 21, 22 and 23 proceeds
10 according to the flowchart of Fig. 7 and the operation of the traffic
11 management center 50 proceeds according to the flowchart of Fig. 8.

12 If a user encounters a congestion in the initially selected network (step
13 501), the selected network sends a request signal to the traffic management
14 center 50 (step 502). When the controller 51 of management center receives
15 the request signal from one of the networks 21, 22, 23 (step 601), it reads user
16 information from the database 52 (step 602) to determine whether the user is
17 entitled to access other networks (step 603). If the user is not entitled to
18 access other networks, flow proceeds from step 603 to step 610 to send a busy
19 message to the requesting network, and returns to the starting point of the
20 routine. If the decision at step 603 is affirmative, flow proceeds to step 604 to
21 compare the congestion levels of other networks with a predefined threshold
22 level and determines if the congestion level of a network is lower than the
23 threshold level (step 605). If this is the case, flow proceeds from step 605 to
24 step 606 to check to see if all other networks have been tested. If not, flow
25 returns to step 604 to repeat the comparison step on the next network. If all

1 other networks have been tested, flow proceeds to step 607 to determine the
2 network having a least routing cost, and the controller 51 sends a rerouting
3 message to the requesting network (step 608). If the congestion levels of all
4 other networks are higher than the threshold, flow proceeds through steps
5 605 and 609 to step 610 to send a busy message to the requesting network.

6 When the requesting network receives a rerouting message or a busy
7 message from the traffic management center 50 (step 503), it retransmits the
8 receive message to the requesting user as a response signal (step 504) and
9 returns to the starting point of the routine.

10 When the user receives a response signal from the initially selected
11 network, the user terminal 20 may be switched to another interface for re-
12 establishing a connection.